






LIN-05 高精度直线轴承座 LIN-05 Precision linear bearing



订购编码 Order P/N	轴 Axis mm ²	公差 Tolerance mm ²	F max. 动态 P=5 MPa	F max. 静态 P=35 MPa	重量 Weight g
LIN-05-12	12	可调	840	5,880	78
LIN-05-16	16	可调	1,200	8,400	106
LIN-05-20	20	可调	1,500	10,500	132
LIN-05-25	25	可调	2,500	17,500	253
LIN-05-30	30	可调	3,750	26,250	374
LIN-05-40	40	可调	6,000	42,000	713
LIN-05-50	50	可调	8,750	61,250	1,168

装配尺寸 Installation size

订购编码 Order P/N	d1	H +0.01 -0.014	H1	A	M	E ± 0.15	E1 ± 0.15	S	S1	S2	Sb	N1	N2	L
LIN-05-12	12	17	33	40	20.0	29	18.0	8.0	4.3	M5	2	16	11	28
LIN-05-16	16	19	38	45	22.5	34	19.0	8.0	4.3	M5	2	18	11	30
LIN-05-20	20	23	45	53	26.5	40	20.0	9.5	5.3	M6	2	22	13	30
LIN-05-25	25	27	54	62	31.0	48	25.5	11.0	6.6	M8	2	29	18	50
LIN-05-30	30	30	60	67	33.5	53	30.5	11.0	6.6	M8	2	29	18	50
LIN-05-40	40	39	76	87	43.5	69	36.0	15.0	8.4	M10	2	38	22	60
LIN-05-50	50	47	92	103	51.5	82	44.0	18.0	10.5	M12	2	46	26	70



订购编码 Order P/N: LIN-05-12

内径 Inner diameter

标准开口系列 05
Standard series05